


NORMA Ball Valve



**Exceeding performance,
even in harsh sunny conditions**

- ✓ Smooth open and close action to allow or stop the flow of water
- ✓ High quality glass reinforced polyamide construction
- ✓ Interchangeable handles to comply with international colour coding for water

Save from purchasing additional fittings with the male / female version!

-  Non-corrosive and UV stabilized material making it suitable for severe conditions
-  Removable handle making the valve inoperable for security reasons
-  Maximum operating temperature of 60° C
-  Pressure rating 16 bar

NORMA Ball Valve - Female / Female	NORMA Ball Valve - Male / Female
F/F Ball Valve 15 mm / 1/2"	M/F Ball Valve 20 mm / 3/4"
F/F Ball Valve 20 mm / 3/4"	M/F Ball Valve 25 mm / 1"
F/F Ball Valve 25 mm / 1"	M/F Ball Valve 32 mm / 1 1/4"
F/F Ball Valve 32 mm / 1 1/4"	M/F Ball Valve 40 mm / 1 1/2"
F/F Ball Valve 40 mm / 1 1/2"	M/F Ball Valve 50 mm / 2"
F/F Ball Valve 50 mm / 2"	

Love what you see? Here are some more products you may like.



NORMA PC Dripline



NORMA PN 10



NDS Valve Box

You need help or want to know more? Feel free to consult our specialists!



+44 1635 521880



watermanagement@normagroup.com



norma-watermanagement.com



NORMA Group Holding GmbH | Edisonstraße 4 | 63477 Maintal | Germany | norma-watermanagement.com

This document supersedes all previous issues. No part of this publication may be reproduced without our prior written consent. In NORMA Group's policy of continual product improvements to meet user needs and technological developments, all models and sets listed in this file (photographs, specifications, sizes and weights) may be upgraded or discontinued without notice and without any obligation on our part to modify tools or equipment sold previously. The recommendations for use and safety given in this file do not replace accepted good practice or the safety related legal and regulatory provisions. References to standards implemented as of 1 December 2018 are not contractually binding.