

NORMA CV Dripline 16 & 17 mm



Durable under harsh field conditions

- ✓ Superior performance and lower maintenance
- ✓ Faster and easier to install
- ✓ Chemical-free root intrusion protection



Reduce material and labour!

- ✓ With low opening pressure of 0.5 bar and efficient emitter design, NORMA CV Dripline with check valve works with all applications such as landscapes, hillsides, raised planters, etc.
- ✓ Anti-siphon mechanism prevents suction of sand and soil into the emitter
- ✓ Simplifies the design and installation process
- ✓ Minimal clogging due to self-flushing emitter design

NORMA CV Dripline 16 & 17 mm

Flow rate: 2.1 lph

Emitter spacing: 30 cm

Coil size: 50 m & 100 m

Love what you see? Here are some more products you may like.



AccuFlow™ PC



Adjustable Flow Rate Emitter



Smart-Loc™ Compression Fitting

You need help or want to know more? Feel free to consult our specialists!



+44 1635 521880



watermanagement@normagroup.com



norma-watermanagement.com



NORMA Group Holding GmbH | Edisonstraße 4 | 63477 Maintal | Germany | norma-watermanagement.com

This document supersedes all previous issues. No part of this publication may be reproduced without our prior written consent. In NORMA Group's policy of continual product improvements to meet user needs and technological developments, all models and sets listed in this file (photographs, specifications, sizes and weights) may be upgraded or discontinued without notice and without any obligation on our part to modify tools or equipment sold previously. The recommendations for use and safety given in this file do not replace accepted good practice or the safety related legal and regulatory provisions. References to standards implemented as of 1 December 2018 are not contractually binding.